

2021 NEW PRODUCT DESCRIPTION

2021新品速递



出口全球129个国家和地区

"RUNXIN Valve" has been exported to 129 countries and regions in the world

F92 控制阀新外观

New appearance of control valve

RUNXIN

- ① 小阀体 大流量
Small valve body, big flow rate
- ② 0.1MPa压差下，流量4.7m³/h
Under 0.1MPa pressure drop, the flow rate is 4.7m³/h
- ③ 逆流再生，省盐省水
Up-flow regeneration, save water and salt
- ④ 防尘罩采用卡扣式连接
Dust cover adopts clamp connection
- ⑤ 6种再生模式可选
6 regeneration modes are available



F116 控制阀新外观

New appearance of control valve




- ① 0.1MPa压差下，流量4m³/h
Under 0.1MPa pressure drop, the flow rate is 4m³/h
- ② 防尘罩采用卡扣式连接
Dust cover adopts clamp connection
- ③ 时间型和流量型可选
Time clock type and meter type are available






- ① 专利设计一阀多罐串联系统
Patented design: one valve on duplex tanks, working in series
- ② 0.1MPa压差下，流量4m³/h
Under 0.1MPa pressure drop, the flow rate is 4m³/h
- ③ 可选净化+软化双罐串联系统
Filter + softening duplex tanks work in series system
- ④ 可选臭氧+过滤双罐串联除铁锰系统
Ozone + filter duplex tanks for iron and manganese removal system works in series
- ⑤ 可选双罐串联软化系统
Duplex tanks softener system works in series
- ⑥ 可实现三罐或以上的多罐串联处理
Three or more tanks can be realized in series



双罐串联系统
Duplex Tanks
Work in Series



三罐串联系统
Three Tanks
Work in Series

技术参数 | Parameters

型号 Model	进水口 Inlet	出水口 Outlet	排水口 Drain	吸盐口 Brine tank connector	基座 Base	中心管 Riser pipe	运行流量m³/h @0.1MPa Service flow rate @0.1MPa
F142	G1	G1	NPT3/4	G3/8	2.5"-8 NPSM	1"D-GB (Ø32)	4

泳池过滤阀

Swimming pool filter valve

RUNXIN

- 1 陶瓷端面密封结构，耐磨损、耐腐蚀
Hermetic head faces structure, good performance in wear and corrosion resistance
- 2 采用顶装、卡箍式连接
Adopt top-mounted structure, **clamp connection**
- 3 进、出、排水口胶粘方式连接
Inlet, outlet and drain **adopt glue connection**
- 4 可选手动和自动控制
Manual and automatic control is available
- 5 具有过滤、反洗、正洗、排空、循环、关闭等六种功能
With 6 functions, including filter, backwash, fast rinse, waste, recirculation, closed



技术参数 | Parameters

型号 Model	接口尺寸Connector size			反洗流量m ³ /h @0.1MPa Backwash flow rate@0.1MPa	备注 Remark
	进/出/排水口胶接 Glued inlet/outlet/drain	基座 Base	中心管 Riser pipe		
F139	2"D-GB (外径63.3 mm UPVC管) 或 2.375"OD (外径60.3mm UPVC管)	卡箍方式 (适用罐内 直径149mm)	1.5"D-GB (外径50mm) 或1.9" OD (外径48.3mm)	24	自动 (压力或时间 启动反冲洗) Automatic (pressure or time to control backwash)
F139S	2"D-GB (63.3mmOD UPVC pipe) Or 2.375"OD (60.3mmOD UPVC pipe)	Clamp connection (suitable for tank open with inner diameter 149mm)	1.5"D-GB (50mm OD) Or 1.9"OD (48.3mm OD)		手动 Manual

注：F139适用的电源适配器输出为：DC24V、1.5A。

Remark: the output of F139 transformer is DC12V,1.5A.

温州市润新机械制造有限公司
WENZHOU RUNXIN MANUFACTURING MACHINE CO.,LTD

地址：浙江省温州市山福镇润新路169号

No.169, Runxin Road, Shanfu Town, Wenzhou, Zhejiang, China

电话 (Tel) : +86-577-88635628 88630038 邮编 (P.C) : 325021

传真 (Fax) : +86-577-88633258 E-mail:sales@run-xin.com



400-000-2895

www.run-xin.com