



PWG MEMBRANES

MADE TO BE DIFFERENT

4021HF - HIGH FLOW

Based on our extensive knowledge and experience in distribution, we have selected a limited range of pure water membranes. Our object is to offer you high quality products at a competitive price, while promising excellent availability. If you need any other membranes contact our sales team and we will do our best to fulfil your needs.



PWG MEMBRANES

MADE TO BE DIFFERENT

LOW PRESSURE MEMBRANE

Reference	Flow*		Nominal Salt Rejection
	gpd	l/h	
1112020002	1450	228	99


Available at a temperature of 25 °C under the following conditions:

NaCl solution 1500 ppm TDS - applied pressure 10,3 bar (150 psi) - temperature 25 °C - permeate recovery: 10% - pH range: 6.5 - 7.0

OPERATING LIMITS

- Pressure Tape wrap: 20,7 bar - 300 psi
- Temperature: 45°C
- Pressure drop: 0,7 bar - 10 psi
- Feed flow: 12 gpm or 2,7 m³/h
- Chlorine Concentration: < 0,1 ppm
- Feedwater SDI (15 min): < 5
- Feedwater Turbidity: < 1 NTU
- Feedwater pH: 3 - 10
- Min ratio concentrate to permeate flow for any element: 5 :1

4021



A	Length	533,4 mm
B	ATD Diameter	100,3 mm
C	Connection Diameter	19,1 mm
Df	Core Tube Ext Feed Side	30,5 mm
Dc	Core Tube Ext Conc Side	30,5 mm
	Weight	1,8 kg

