

◎专利号(Patent): ZL201320732225.7



# 陶瓷硬密封球阀

— Ceramic Hard Sealing Ball Valve —

**硬密封**

Hard sealing

**轻扭矩**

Low torque

**耐腐蚀**

Good corrosion resistance

**耐磨损**

Good wear resistance



**启闭很轻松**

Open and close easily

**2021新品**

New product of 2021



## V形电动调节球阀

V Type Electronic Adjustable Ball Valve


- V形孔流动
- 等百分比流量特性
- 可选DC24V直流或AC220V控制
- V type flow channel
- Equal percentage flow characteristics
- DC24V or AC220V controlling is optional



## AC220V带位置反馈电动球阀

AC220V Ball Valve with Position Feedback

- AC220V电源控制
- 三线控制，带位置反馈
- 适用不同阀体和接头形式
- AC220V power control
- Three-wire controlling, with position feedback
- Suitable for different valve bodies and connection ways



● AC220V 金属 Metal





● AC220V 塑料 Plastic

DN15-DN100

## 气动T形三通球阀DN25

T Type Pneumatic Three-way Ball Valve DN25

- 4种流向可选
- PPH热熔接头
- 陶瓷硬密封结构
- 耐腐蚀、耐磨损
- 4 kinds of flow direction options
- PPH hot melt connector
- Ceramic hard sealing structure
- Good corrosion resistance, good wear resistance



## 卡箍连接球阀系列

Clamp Connection Ball Valve Series

- DIN11850卫生级卡箍式连接
- 陶瓷硬密封结构
- DN15-DN50
- DIN11850 sanitary clamp connection
- Ceramic hard sealing structure
- DN15-DN50



## 三通球阀DN65/DN80

Three-way Ball Valve DN65/DN80



• Q934513-65/80

- 陶瓷硬密封，耐腐蚀、耐磨损、耐久用
- UPVC阀体、胶粘接头、由令活接
- L型三通结构，手动、自动和气动可选
- Ceramic hard sealing, good corrosion resistance, Wear resistant, long Life
- UPVC valve body, adhesive joint, animated connector
- L Type three-way structure, manual, automatic and pneumatic optional

## 碳化硅球阀

Silicon Carbide Ball Valve


- 2200℃超高温烧结
- 耐强酸和强碱，耐高温，耐磨损
- 具有硬度高、高温热稳定性、低膨胀系数和抗热震性等优良特性；
- 低摩擦系数，启闭更轻松
- Made by high sintering at 2200℃
- Resistant to strong acid and alkali, high temperature and abrasion;
- It has many excellent features such as high hardness and high thermo stability, Low coefficient of expansion and good thermal shock resistance.
- Low coefficient of friction, open and close easily



## 气动球阀

Pneumatic Ball Valve

- 启闭速度快（约1-2s），可配调速器来调节启闭速度
- Fast opening and closing speed (about 1-2s), can be equipped with a speed controller to adjust the speed.



DN15-DN100

## 过滤&软化/混床球阀控制器

Ball Valve Controller for Filter & Softener and Mixed Bed Water Treatment Systems



型号: 46030(F109)  
 Model 46040(F109B)

**过滤**  
 控制系统  
 Filter control system



**软化**  
 控制系统  
 Softener control system



**混床**  
 控制系统  
 Mixed bed control system



- ◎可与本公司DN20 ~ DN80的电动球阀配套使用;
- ◎配套用的陶瓷芯电动球阀, 流阻小、耐腐蚀、抗水垢抗杂质、耐久用;
- ◎LCD显示界面。
- ◎It can be used together with Runxin electronic ball valve from DN20 to DN80.
- ◎The matched ceramic ball valve has the advantage of small flow resistance, good corrosion resistance, good wear resistance and long lifetime.
- ◎LCD display.

◎ 本公司保留更改产品设计与规格的权利 产品外观及参数若有不符,请以实物为准。  
Product appearance, specification and parameter, please be subject to the real product.



## 出口全球 24 个国家和地区

Ceramic ball valve has been exported to 24 countries and regions in the world.



**温州市润新机械制造有限公司**  
WENZHOU RUNXIN MANUFACTURING MACHINE CO.,LTD

地址: 浙江省温州市山福镇润新路169号

No.169, Runxin Road, Shanfu Town, Wenzhou, Zhejiang, China

电话 (Tel): +86-577-88576511 88630038

邮编 (P.C): 325021

传真 (Fax): +86-577-88633258

E-mail: sales@run-xin.com



# 400-000-2895

[www.run-xin.com](http://www.run-xin.com)