

Eva SXT

Purely Soft Water



Eva SXT

Eva SXT is a range of softeners assembled with the Pollet Water Group exclusive Eva cabinet. This unit has a large LCD display for good readability and straightforward step-by-step programming. The controller is easy to service yet very accurate thanks to the optical sensors. Eva SXT softeners are available from stock in 5 different sizes and 3 different colours.

FEATURES

-  **PWG EXCLUSIVE**
cabinet
-  **CLEAN LOOK**
with glossy cover
-  **SMALL FOOTPRINT**
-  **USER FRIENDLY**
Handles for easy moving
-  **EASY SALT FILLING**
due to tilting salt lid
-  **THREE SIZES**
Mini, Midi & Maxi
-  **TRANSPARENT WINDOW**
good visibility valve

COLOURS





COMPOSITION

The Eva sXT softeners come with:

- Fleck 5600SXT electronic volumetric valve
- Eva Tilting Lid Cabinet
- Composite vessel with distributor & tube
- Heterodisperse resin
- Bypass 1" inox
- Brine well & safety brine valve 2310

Note: The configuration as mentioned above is available from stock.
For personalised units, please contact us for more information on price and delivery time.

ORDER REFERENCE	ITEM NAME	DIMENSIONS (W X D X H) IN MM
MINI		
4201010001	Eva sXT Mini 10L	300 x 500 x 741
4201010002	Eva sXT Mini 14L	300 x 500 x 741
MIDI		
4201010003	Eva sXT Midi 18L	300 x 500 x 1072
MAXI		
4201010004	Eva sXT Maxi 22L	300 x 500 x 1200
4201010005	Eva sXT Maxi 30L	300 x 500 x 1200

FEATURES CONTROLLER

- **Large LCD display**
Good readability
- **Simple servicing**
Special seal & spacer design
- **Easy step-by-step Programming**
- **Precise Performance**
Optical sensors control the backwash cycle



TECHNICAL SPECIFICATIONS SOFTENER

MODEL	MINI		MIDI	MAXI	
Dimensions mm (H x W x D)	741 x 300 x 500		1072 x 300 x 500	1200 x 300 x 500	
Exchange capacity (kg CaCO ₃)	0.32	0.48	0.84	1.15	1.62
Control System	Fleck 5600SXT		Fleck 5600SXT	Fleck 5600SXT	
Regeneration type	Downflow		Downflow	Downflow	
Tank Size	8x17	10x17	8x30	8x35	10x35
Unit Size	10	14	18	22	30
Service Flow Rate (m ³ /h)	0.7	1.0	1.3	1.5	2.1
Peak Flow Rate (m ³ /h)	1.6	2.5	1.6	1.6	2.5
Water Used / Regeneration (L)	50	76	81	94	136
Plumbing Connections	1"		1"	1"	
Electrical Rating	220V/50Hz		220V/50Hz	220V/50Hz	
Water Supply	Municipal		Municipal	Municipal	
Water Temperature	1 - 35°C		1 - 35°C	1 - 35°C	
Operating Pressure	2 - 6 bar		2 - 6 bar	2 - 6 bar	